

Via Galvani, 14 - 20094 Corsico (MI) - Italy Tel. (+39) 02 45864035 - Fax (+39) 02 45869840 e-mail: info@pandoralloys.com Internet: www.pandoralloys.com





Classic Casting

DATA SHEET

TECH

9 kt

**GENERAL INFORMATION** 

Carats: Colour: 9 kt, suitable also for 14kt and 18 kt (see specific tech data) Red Colour coordinates: L\*=84.0 a\*=9.1 b\*=15.0

Advised use:

CASTING	clos syst		open systems	pre-set stones	
Density:	12,72 g/c	°m³			
Hardness (as cast): Hardness (after annealing):	120 HV 130 HV				
DIRECTIONS FOR SUGGESTE	D USE				

Casting

Melting temperature: 980 °C

Casting temperature:

100 °C over its melting temperature to cast with centrifugal machines.

120 °C over its melting temperature to cast in vacuum machines with controlled atmosphere. 140 °C over its melting temperature to cast in outdoor cylinders with vacuum.

Cylinders temperature:	from 550 °C to 650 °C depending on the machine and objects dimensions
Cooling casted objects:	in water after 10 minutes
Annealing:	660 °C for 20 minutes followed by a quick cooling in hot water (40 °C min.)

The above directions are only indicative. Strong variations to the above data are possible, depending on personal experience. Please, do not hesitate to contact us for further information.