

**A/M**



**Classic Mechanical**

**14kt**

## GENERAL INFORMATION

Carats: 14kt, suitable also for 18kt (see specific tech data sheet)  
 Colour: off white  
 Advised use: mechanical works

MECHANICAL WORKS	stamping	■	chains	■	tube	■	spring	■
------------------	----------	---	--------	---	------	---	--------	---

Density: 12,75 g/cm<sup>3</sup>  
 Hardness (as cast): 125 HV  
 Hardness (after cold work 70%): 240 HV  
 Hardness (after annealing): 120 HV

Nickel release UNI EN 1811:2011: Nickel release test on finished objects is required

## DIRECTIONS FOR SUGGESTED USE

Melting temperature: 970 °C

Casting temperature:  
 80 °C over its melting temperature for continuous casting with sinker thermocouple.  
 100 °C over its melting temperature to cast into ingot-mould and continuous casting.

Ingot-mould temperature: 150 °C

Cooling of ingots: quick in lukewarm water (about 40 °C)

Annealing: 700 °C for 20 minutes followed by a quick cooling in hot water (40 °C min.), better if with alcohol

## HINTS

- ❖ Recommended Pandora Alloys 14kt white solders: TB14 (soft), MB14 (medium), FB14 (hard)
- ❖ Suggested Pandora Alloys plating solutions: Rhodium P2 and Palladium PDSOL/BE

The above directions are only indicative. Strong variations to the above data are possible, depending on personal experience. Please, do not hesitate to contact us for further information.