

EASY/ECO



High Performance Casting

18kt

GENERAL INFORMATION

Colour: white - standard
 colour coordinates: L*=85.5 a*=2.8 b*=14.5

Advised use: casting

CASTING	closed systems	■	open systems	■	pre-set stones	■
---------	----------------	---	--------------	---	----------------	---

Density: 14,56 g/cm³
 Hardness (as cast): 175 HV

Nickel release UNI EN 1811:2011: 0,14 µg/cm²/week – **COMPLIANT** (max. 0.88 µg/cm²/week)

DIRECTIONS FOR SUGGESTED USE

Melting temperature: 920 °C

Casting temperature:

100 °C over its melting temperature to cast with centrifugal machines.

120 °C over its melting temperature to cast in vacuum machines with controlled atmosphere.

140 °C over its melting temperature to cast in outdoor cylinders with vacuum.

Cylinders temperature: from 550 °C to 650 °C depending on the machine and objects dimensions

Cooling casted objects: in water after 5 minutes
 Cooling casted objects (with stones): in water after 30/40 minutes

HINTS

- ❖ Recommended Pandora Alloys 18kt white solders: TB18 (soft), MB18 (medium), FB18 (hard)
- ❖ Suggested Pandora Alloys plating solutions: Rhodium P2 and Palladium PDSOL/BE

The above directions are only indicative. Strong variations to the above data are possible, depending on personal experience. Please, do not hesitate to contact us for further information.